KEWTECH

キューテック

KT220

CURRENT CLAMP FOR PV INSTALLATIONS AND HVAC



EMPOWERING YOUR EXPERTISE!



KT220
CURRENT CLAMP FOR PV INSTALLATIONS AND HVAC

FEATURES

- ACV 1500V/DCV 2000V and DCmV
- Resistor/Continuity
- Capacitor/Diode
- Frequency
- Min/Max
- Volt Seek
- HFR/INRUSH
- Backlight
- PV Voltage
- Torch light
- Data logger
- Bluetooth
- ACA/DCA 1500A and AC/DCµA
- Temperature -40°C till +400°C

PV TESTLEAD (KTALTPV) INCLUDED



SECTION	OL READING	RESOLUTION	ACCURACY
DC mV			
600,0mV	660.mV	0,1mV	+(0,7%+5D)
DC Voltage			
600,0V	600,0V	0,1V	+(0,7%+2D)
1000V	1100V	1V	
AC Voltage			
600,0V	600,0V	0,1V	+(1,0%+5D)
1000V	1100V	1V	
LoZ AC/DC Voltage			
600,0V	600,0V	0,1V	+(2,0%+5D)
1000V	1100V	1V	
PV DC Voltage			
600,0V	600,0V	0,1V	+(2,0%+5D)
2000V	2200V	1V	
PV AC Voltage			
600,0V	600,0V	0,1V	+(2,0%+5D)
1500V	1600V	1V	
AC/DC µA			
400,0µA	400,0µA	0,1µA	+(1,0%+3D)
400,0µA	400,0µA	1µA	
DC Current			
60,00A	66,00A	0,01A	+(2,0%+5D)
600,00A	660,0A	0,1A	
1500A	1550A	1A	
AC Current			
60,00A	66,00A	0,01A	+(2,0%+5D)
600,00A	660,0A	0,1A	
1500A	1550A	1A	
Flexible current clamp			
300,0A	330,0A	0,1A	+(1,5%+5D)
3000A	3300A	1A	
Frequency			
100,00Hz	100,00Hz	0,01Hz	+(0,3%+3D)
1000,00Hz	1000,0HZ	0,1Hz	
10,000Hz	10,000kHz	0,001kHZ	
High Frequentie Rejection			
Available for ACV, ACA and flexible current clamp			
Inrush current			
Available for ACA and Flexible current clamp, activation level : ≥50d.			
Resistance			
600,0Ω	660,0Ω	0,01 Ω	+(0,9%+5D)
6,000kΩ	6,600kΩ	0,001k Ω	
60,00kΩ	66,00kΩ	0,00k Ω	
600,0kΩ	660,0kΩ	0,1k Ω	+(0,9%+2D)

KEWTECH
キューテック

Exclusive distributor for Belgium:

CCI nv

CCI nv, Louiza-Marialei 8/5, 2018 Antwerp | T: +32 (0)3 232 78 64 | info@ccinv.be | **www.ccinv.be**